

XS pH 60 VioLab Bench pHmeter - without electrode

Item Code: 50101112



DATA SHEET

Features

Accuracy (pH)	± 0,02 pH
Accuracy (Temperature)	± 0,5 °C
Power supply	100 - 240 V
AQA calibration	Yes
DHS compatibility	Yes
Temperature compensation	0,0 ... +100,0 °C
Temperature compensation (auto - manual)	Yes
PC Communication	Micro USB
Criteria for stability of the measure	Low - Med - High

With accessories, S7-BNC cable and NT 55 temperature probe, without electrode

Description	
Display	High-definition, backlit colour LCD
Frequency	50 - 60 Hz
AQA	Yes
IP rating	54 IP
Calibration data indication	Yes
Buffer used indication	Yes with icon
Inputs	BNC - RCA
Memory / Datalogger	1000
Name	pH 60 VioLab
Parameters	pH - mV - ORP - T
Weight	0.38 kg
ORP calibration points	1
PH calibration points	1 ... 3 automatic values - 2 user values
Measuring range mV	-1000 ... +1900 mV
mV ORP measuring range	-1000 ... +1900 mV
pH measuring range	-2,00 ... +16,00 pH
temperature measurement range	-10,0 ... +110,0 °C

EDM Ltd.

โทรศัพท์ : 02 966 1590 มือถือ : 086 316 7625

Email : contact@edm.co.th LINE ID : EDM9824

Calibration Report	Yes, printable
ORP resolution	0.1 / 1 (automatic scale) mV
pH resolution	0,1 / 0,01 pH
Temperature resolution	0,1 °C
Recognised pH buffers	USA - NIST
Working temperature	0 ... +45 °C
Timer calibration due with alarm	Si

DS_50101112_rev. _16-12-2024

EDM Ltd.

โทรศัพท์ : 02 966 1590 มือถือ : 086 316 7625

Email : contact@edm.co.th LINE ID : EDM9824