

# XS pH 7 Vio portable pHmeter - Electrode 201 T

Item Code: 50110012



## DATA SHEET

### Features

Accuracy (pH)	±0,02 pH
Accuracy (Temperature)	±0,5 °C
Power supply	3 x AA batteries 1.5 V
DHS compatibility	Yes
Temperature compensation	0,0 ... +100,0 °C
Temperature compensation (auto - manual)	Yes
Criteria for stability of the measure	Low - Med - High
Description	Complete with XS 201 T electrode, with integrated temperature sensor
Suitcase dimensions	360 x 300 x 130 mm
Display	High-definition, backlit colour LCD
IP rating	57 IP
Calibration data indication	Yes
Buffer used indication	Yes with icon
Inputs	BNC - RCA
Name	pH 7 Vio
Parameters	pH - mV - ORP - T
Weight	0.4 kg
Weight (in suitcase)	1.72 kg
ORP calibration points	1 Automatic
PH calibration points	1 ... 3 automatic values - 2 user values
Measuring range mV	-1000 ... +1000 mV
mV ORP measuring range	-1000 ... +1000 mV
pH measuring range	0,00 ... 14,00 pH
temperature measurement range	0,0 ... +100,0 °C
Calibration Report	Yes
ORP resolution	1 mV
pH resolution	0,1 / 0,01 pH

**EDM Ltd.**

โทรศัพท์ : 02 966 1590 มือถือ : 086 316 7625

Email : contact@edm.co.th LINE ID : EDM9824

Temperature resolution	0.1 °C
Auto off	After 20 minutes
Recognised pH buffers	USA - NIST
Working temperature	0 ... +45 °C

---

*DS\_50110012\_rev.\_14-12-2024*

**EDM Ltd.**

โทรศัพท์ : 02 966 1590 มือถือ : 086 316 7625

Email : [contact@edm.co.th](mailto:contact@edm.co.th) LINE ID : EDM9824