

XS COND 7 Vio portable conductivity meter - Cell 2301 T

Item Code: 50110412



DATA SHEET

Features

| | |
|-------------------------------|---|
| Accuracy (Cond) | ±2 % f.s. |
| Accuracy (TDS) | ±1 % f.s. |
| Accuracy (Temperature) | ±0,5 °C |
| Power supply | 3 x AA batteries 1.5 V |
| Temperature coefficient (max) | 0,00 ... 10,00 % / °C |
| Temperature compensation | 0,0 ... 100,0 °C |
| Cell constant | 0.1 - 1 - 10 |
| Description | Complete with 2301T cell with built-in temperature sensor, 1 m fixed cable |
| Suitcase dimensions | 360 x 300 x 130 mm |
| Display | High-definition, backlit colour LCD |
| TDS factor | 0.40 ... 1.00 |
| IP rating | 57 IP |
| Buffer used indication | Yes with icon |
| Inputs | BNC - RCA |
| Name | Cond 7 Vio |
| Weight | 0.4 kg |
| Weight (in suitcase) | 1.72 kg |
| Suitcae weight | 1.65 kg |
| Calibration points Cond | 1 ... 4 automatic values - 1 user value |
| Cond measuring range | 0.00 µS ... 200 mS |
| TDS measuring range | 0.1 mg/l ... 200 g/l |
| temperature measurement range | 0.0 ... 100.0 °C |
| Calibration Report | Yes |
| Cond resolution | 0,01 / 0,1 / 1 (scala automatica) µS/cm - mS/cm |
| Temperature resolution | 0.1 °C |
| Auto off | After 20 minutes |
| Swabs recognised Cond | 84 µS - 147 µS - 1413 µS - 12,88 mS - 111,8 mS |

EDM Ltd.

โทรศัพท์ : 02 966 1590 มือถือ : 086 316 7625

Email : contact@edm.co.th LINE ID : EDM9824

| | |
|-----------------------|----------------|
| Working temperature | 0 ... +45 °C |
| Reference temperature | +15 ... +30 °C |
| Cell type | 2 rings |

DS_50110412_rev. _14-12-2024

EDM Ltd.

โทรศัพท์ : 02 966 1590 มือถือ : 086 316 7625

Email : contact@edm.co.th LINE ID : EDM9824