

XS COND 70 Vio portable conductivity meter - Cell 2301 T

Item Code: 50110512



DATA SHEET

Features

Accuracy (Cond)	±2 % f.s.
Accuracy (Salinity)	±1 % f.s.
Accuracy (TDS)	±1 % f.s.
Accuracy (Temperature)	±0,5 °C
Power supply	3 x AA batteries 1.5 V
Temperature coefficient (max)	0,00 ... 10,00 % / °C
Temperature compensation	0,00 ... 100,00 °C °C
PC Communication	Micro USB
Automatic brightness control	Yes
Cell constant	0,1 - 1 - 10
Description	Complete with 2301T cell with built-in temperature sensor, 1 m fixed cable
Suitcase dimensions	360 x 300 x 130 mm
Display	High-definition, backlit colour LCD
TDS factor	0,40 ... 1,00
AQA	Yes
IP rating	57 IP
Buffer used indication	Yes with icon
Inputs	BNC - RCA
Memory	1000
Name	Cond 70 Vio
Output	Micro USB
Weight	0.4 kg
Suitcae weight	1.65 kg
Calibration points Cond	1 ... 4 automatic values - 1 user value
Cond measuring range	0,00 µS ... 200 mS
Salinity measuring range	0,1 ppm ... 100 ppt
TDS measuring range	0.1 mg/l ... 200 g/l

EDM Ltd.

โทรศัพท์ : 02 966 1590 มือถือ : 086 316 7625

Email : contact@edm.co.th LINE ID : EDM9824

temperature measurement range	-10,0 ... +110,0 °C
Cond resolution	0,01 / 0,1 / 1 (scala automatica) $\mu\text{S}/\text{cm}$ - mS/cm
Temperature resolution	0.1 °C
Calibration due with alarm	Yes
Auto off	After 20 minutes
Swabs recognised Cond	84 μS - 147 μS - 12,88 μS - 111,8 μS
Working temperature	0 ... +45 °C
Reference temperature	+15 ... +30 °C
Timer calibration due with alarm	Si
Cell type	2 rings

DS_50110512_rev. _14-12-2024

EDM Ltd.

โทรศัพท์ : 02 966 1590 มือถือ : 086 316 7625

Email : contact@edm.co.th LINE ID : EDM9824